

# 其他附件

## 蒸馏系统连接图 (适用于RE100-Pro&RE100-S)



C410



### 密封圈及其它附件

#### C410防腐隔膜真空泵

##### 技术参数

极限真空压力: 13mbar

工作模式: 连续

接口规格: 8mm 功率: 95W

电机转速: 1450rpm

抽气速度:

mbar	1000	880	750	600	480	280
L/min	25	22	20	12	7.5	5

噪声: 50分贝

货号	描述	
18204186	真空密封圈 (PTFE+氟橡胶)	
18204187	蒸发瓶弹簧	
18900190	蒸发瓶夹 (红色) CS002440	
18900188	蒸发瓶夹 (绿色) CS002942	
18901001	蒸发瓶夹 (黑色), 适配3L/5L蒸发瓶 NS24/40	
18901002	蒸发瓶夹 (黑色), 适配3L/5L蒸发瓶 NS29/32	
18900871	冷却水硅胶管路, 8mm×12mm+保温层 (长1.8米), 适配CCP5/17/20E	
18900879	二次冷凝器组件, 铁架台+冷凝器+ 真空缓冲罐+收集瓶 (500mL)	
18900744	旋蒸防护罩组件 (适配RE100-Pro)	
18900789	旋蒸防护罩 (RE100-S)	

#### 真空调节器/湿气分离器

货号	描述	
18900186	安装在VC100和真空控制系统中 材质: PVDF, PTFE, ABS, 硼硅酸盐玻璃, 不锈钢	